

# STETCO<sup>®</sup>

**920 Series**

**950 Series**

**Combination Machine with Jetting  
Powerful Hydraulic Buckets**



**POWER | PERFORMANCE | PREPAREDNESS**

# Customize a Stetco CBC to meet your municipal demands.

---



## Stetco 920SP

- Mounts on 19,500-22,500 lb GVWR truck
- 14' hydraulic outreach
- 3 cubic yard stainless steel debris body
- 35' digging depth



## Stetco 950 Series

- Mounts on minimum 33,000 lb GVWR chassis
- Up to 15' hydraulic outreach
- 6-7 cubic yard stainless steel debris body
- Available digging depths up to 100' below ground



## Stetco 950 Hook Series

- Mounts on hook lift skid for fleet versatility, multi-uses of chassis for cost savings
- Up to 15' hydraulic outreach
- 5 cubic yard stainless steel debris body
- 35' digging depth



## Stetco Combination Machine

- Stetco 950 Series
- 5 cubic yard stainless steel debris body
- High pressure, low volume jetting system to handle lateral up to 18" diameter
- Up to 4000 PSI at 12 GPM through 1/2" jetting hose
- 300 gallon water tank
- 300' of jetting hose reel on hydraulically extendable, rotatable turntable

**STETCO...OUR MACHINES DON'T SUCK**

## Simple, Efficient, Smart

Stetco Catch Basin Cleaners (CBC's) clean large volumes of heavy, abrasive, and cumbersome debris from stormwater structures and other collection points—with **zero liquid discharge**. Equipped with rugged hydraulic clam or orange-peel buckets, Stetco machines provide a complementary alternative to vac-trucks, at substantially lower cost of ownership.

Stetco's simple, pragmatic approach provides economical cleaning capabilities that vac-trucks alone cannot match. As a stand-alone solution or to assist vac-trucks with the "heavy lifting," Stetco CBC's reduce stormwater compliance costs and increase your fleet preparedness.



---

## STETCO benefits include:

- Substantially lower cost of ownership
- High uptime, low maintenance
- Pragmatic, no-nonsense design and simple operation
- Buckets squeeze out liquids and load solid debris, not slurry
- No need to carry and discharge water
- Single axle chassis for ease of handling, non-CDL options available
- Quiet operation at low engine RPM
- Easily handles heavy, cumbersome debris that vac-trucks cannot
- Wide range of buckets to fit most structures
- Relieves wear & tear burden on vac-trucks



**Legendary Stetco dependability and value**



**Easily handles heavy debris, squeezes out water simultaneously**

**PROVEN MUNICIPAL PERFORMANCE**





## Stetco buckets provide positive, waterless cleaning power

For example, Stetco buckets easily remove heavy, cumbersome debris that choke vacs. With dry, compact debris, there's no need to add water to handle it—just dig and load. In structures with water present, Stetco buckets dig in and squeeze out water as they close, effectively dewatering the load. Stetco's waterless functionality is a game changer, simplifying operations and conserving water resources.

## Stetco versatility pays off all year long

**A true four-season performer, Stetco can be operated as a dump truck, equipped with plow/spreader gear, and used for secondary debris removal jobs. Available hydraulic tool console powers an array of tools such as paving breakers and sump pumps. Stetco equipment is an all-around performer that earns its keep throughout the year.**

## Quiet operation reduces noise pollution and enhances safety

Stetco equipment efficiently develops cleaning power at relatively low engine RPM, conserving fuel, allowing spoken communication, and reducing excessive noise hazards—much appreciated by operators and residents alike.

## Specifications

General	920SP	950T/13	950T/15
Clear mounting space behind cab	36" (91 cm)	36" (91 cm)	36" (91 cm)
Std. travel height w/hose reel (approx.)	9' (2.7 m)	11' (3 m)	11' (3.35 m)
Aboveground lift height (std.)	21' (6.4 m) max.	21' (6.4 m) max.	21' (6.4 m) max.
Reach below ground (std.)	35' (10.6 m)	35' (10.6 m)	35' (10.6 m)
Installed weight (approx.)	3,000 lb (1,361 kg)	3,700 lb (1,678 kg)	3,900 lb (1,769 kg)
Rotation (std.)	200°	200° or 370°	200° or 370°
Lifting capacities (w/ boom)	2,000 lb (907 kg) @ 14' (4.3 m)	2,850 lb (1,293 kg) @ 13' (4.0 m)	2,250 lb (1,021 kg) @ 15' (4.6 m)
Lifting capacities (w/stabilizers)	5,700 lb (2,586 kg) @ 5' (1.5 m)	8,260 lb (3,746 kg) @ 5' (1.5 m)	8,250 lb (3,742 kg) @ 5' (1.5 m)
Winch lifting capacity (full drum)	2,000 lb (907 kg)	2,000 lb (907 kg)	2,000 lb (907 kg)
Winch line speed	200 fpm (60.9 m/min.)	200 fpm (76.2 m/min.)	200 fpm (76.2 m/min.)
Working pressure	2,050 psi (141 bar)	2,050 psi (141 bar)	2,050 psi (141 bar)
Typical pump capacity	13 gpm (49 L/min)	13 gpm (49 L/min)	13 gpm (49 L/min)
Tank capacity	25 gal (95 L)	37 gal (140 L)	37 gal (140 L)
Retracted boom length	8' (2.44 m)	8' (2.44 m)	7' (2.13 m)
Extended hydraulic boom length	14' (4.3 m)	13.5' (4.1 m)	15' (4.6 m)

Minimum Truck Specifications			
GVWR	19,500 lb (8,845 kg)	33,000 lb (14,969 kg) 35,000 lb (15,876 kg) w/ JetPac	33,000 lb (14,969 kg) 35,000 lb (15,876 kg) w/ JetPac
Front axle	7,000 lb (3,175 kg)	12,000 lb (5,443 kg)	12,000 lb (5,443 kg)
Rear axle	14,700 lb (6,350 kg)	21,000 lb (9,526 kg) 23,000 lb (10,433 kg) w/ JetPac	21,000 lb (9,526 kg) 23,000 lb (10,433 kg) w/ JetPac
Cab to axle	84" (213 cm) for CBC with 8' (2.4 m) body	108" (274 cm) for CBC with 10' (3 m) body 120" (305 cm) for CBC with JetPac and 8' (2.44 m) body	108" (274 cm) for CBC with 10' (3 m) body 120" (305 cm) for CBC with JetPac and 8' (2.44 m) body
Min. RBM		1,650,000	1,650,000

Please submit chassis specifications to factory for approval prior to ordering.

## Available Options:

- Hydraulic and manual boom extensions
- Stabilizers
- Radio remote control
- Deep digger equipment for 50', 75' or 100' (15.2 m, 22.9 m or 30.5 m) below-grade operation
- Stetco hydraulic tool interface and hose reel
- High-pressure, low volume water jetting system
- Low pressure washdown system
- Front-mounted boom rest for use with 370° swing allows unobstructed use of dump body
- Tool boxes
- Bucket baskets
- Hooklift mounting
- Basin spades with storage brackets
- Basin grate removal devices
- Full customizable from factory

## JetPac 2000 System



The Stetco combo unit adds our optional JetPac system.

The high-pressure, low-volume JetPac allows you to jet lateral lines up to 18" (46 cm) in diameter\*. A rugged performer, the pump can be run dry without damage; a recirculation option allows operation in subfreezing temperatures.

\*with 300' of 1/2" jetting hose up to 4000 PSI @ 12GPM



**Orange Peel**



**Rectangular Clamshell**



**Round Clamshell**



Stetco buckets allow high-volume debris removal in minimum time.

## Stetco Bucket Specifications

Model	Orange Peel		Long Blade			Rectangular Clamshell		Round Clamshell	
Outside size	13.5" (34 cm)	15" (38 cm)	15" (38 cm)	18" (46 cm)	24" (61 cm)	12" x 17" (30 cm x 43 cm)	20" x 24" (51 cm x 61 cm)	10.75" (27.3 cm)	12.75" (32.4 cm)
Max. blade opening	33" (84 cm)	36" (91 cm)	43" (109 cm)	40" (102 cm)	48" (122 cm)	30" (76 cm)	35" (89 cm)	36" (91 cm)	34" (86 cm)
Closed height	47" (119 cm)	48" (122 cm)	53" (135 cm)	48" (122 cm)	57" (145 cm)	46" (117 cm)	51" (130 cm)	51" (130 cm)	51" (130 cm)
Open height	43" (109 cm)	44" (112 cm)	48" (122 cm)	43" (109 cm)	51" (130 cm)	44" (112 cm)	48" (122 cm)	45" (114 cm)	45" (114 cm)
Volume capacity	1.0 cu ft (.028 m <sup>3</sup> )	1.3 cu ft (.037 m <sup>3</sup> )	1.8 cu ft (.051 m <sup>3</sup> )	2.0 cu ft (.057 m <sup>3</sup> )	3.0 cu ft (.085 m <sup>3</sup> )	2.0 cu ft (.057 m <sup>3</sup> )	4.0 cu ft (.113 m <sup>3</sup> )	.8 cu ft (.023 m <sup>3</sup> )	1.0 cu ft (.028 m <sup>3</sup> )
Weight (empty)	255 lb (116 kg)	265 lb (120 kg)	280 lb (127 kg)	285 lb (129 kg)	350 lb (159 kg)	285 lb (129 kg)	350 lb (159 kg)	210 lb (95 kg)	250 lb (113 kg)

Ask about other custom sizes.

# Innovation from the Industry leader

---

For over 60 years, Stetco Catch Basin Cleaners have been quietly maintaining stormwater infrastructure in the some of the nation's oldest and most challenging systems. Stetco attributes—including cost, capability and water conservation—make them a valuable tool to tackle operations that vac-trucks alone cannot.

At less than half the cost, Stetco machines make short work of cleaning jobs that can impede, clog, or damage vac-trucks. And total cost of ownership of Stetco equipment is a fraction of that of vac-trucks. Thanks to their relatively simple, no-nonsense design, Stetco equipment is known for its high-uptime and low-maintenance requirements.

Stetco equipment is found in smaller municipalities as a stand-alone compliance solution to federally mandated cleaning of collection systems. In addition, its versatility adds value to smaller, cost-conscious municipalities.

As mission-critical stormwater assets that provide a depth and breadth of cleaning capabilities necessary in complex urban stormwater infrastructure, Stetco machines support vac-trucks in such environments. It's about having the right tool for the job.

Schedule an on-site demonstration to see firsthand how Stetco equipment will enhance your stormwater infrastructure cleaning and compliance capabilities.

## Stetco

- 920 SERIES
- 950 SERIES
- COMBINATION MACHINE WITH JETTING
- POWERFUL HYDRAULIC BUCKETS

## Our reputation is built in.



PO Box 13040 • Spokane, WA 99213  
1(800)892-7831 • Fax (509)533-1050

Serving Washington, Idaho, Montana, Oregon



[www.stetco.com](http://www.stetco.com)