

BALER & COMPACTOR

www.ptrco.com

Stationary Compactors



TP-33SP

Tram-Pak **Stationary Compactor**

Designed For * Retailers * Hospitals * Hotels * * Distribution Centers * * Manufacturing Centers * * Recycling Centers * Home Centers *

Our TP-33SP (Short Profile) compactor was our response to customers battling space constrictions and those who could not accommodate a long chute. We managed to construct a twin cylinder machine with high compaction forces and an overall length of 44 inches. All components are built using heavy-duty structural steel components and welded by AWS certified technicians. The standard unit is ETL approved and has

Specifications

Charge Box Capacity .33 Cu-YD [.25 Cu-m]

Clear Top Opening (L X W) 22 1/2" X 30" [57 cm x 76 cm]

Capacity Per Hour 144 cy/hr

Ram Penetration 4" [10 cm]

Weight 2,850 Lbs [1,292 Kg]

Performance Characteristics

Average Cycle Time 32 sec

Total normal Force 14.022 lbs [62.373 N]

Total Maximum Force 16,497 lbs [73,382 N]

Normal Ram Pressure 19 psi [131 Kpa]

Maximum Ram Pressure 23 psi [159 Kpa]

Electrical Equipment

standard 3 button controls (On/Off key switch, mushroom stop, start button) and a 20' Sealtite.

Electric 208 / 230 / 460 - 3 Phase Control Voltage 110 - 120 Vac

Motor 3 Hp [2.2 Kw]

Hydraulic Equipment

Pump 3.7 GPM [14.0 L/m]

Normal Pressure 1,700 psi [11,721 KPa] Maximum Pressure 2,000 psi [13,790 KPa] (2) Cylinder Bore 2 1/2" [6.3 cm] Cylinder Rod 1 1/4" [3.2 cm]



Serving Washington, Idaho, Montana, Oregon















